- Drive-over circular LED Uplight
- Aluminium body machined from solid in 6082 alloy with surface protection treatment and subsequent polyester powder paint resistant to corrosion, atmospheric conditions and salt spray
- Brushed stainless steel frame AISI 316L
- Thermal shock resistant tempered, extraclear, anti-glare safety glass with grinded edges
- Plastic cable gland resistant to corrosion, atmospheric conditions and salt spray. Silicone gaskets. IP67 external power supply included
- IP68 connector for the connection between projector and power supply included
- IP68 male ad female connectors and neoprene cable for connection extension (between projector and power supply) accessories available on request
- Housing for installation included. No visible screws
- One-step installation without the need to open the fixture
- Maximum permissible ambient temperature +50°C for the 14W and 19W versions, +40°C for the 25W version

- *Proiettore LED circolare a pozzetto carrabile*
- *Corpo in alluminio tornito dal pieno lega 6082 con trattamento superficiale di protezione e successiva verniciatura in polvere di poliestere resistente agli agenti atmosferici, alla corrosione ed alle nebbie saline*
- *Cornice esterna in acciaio inox AISI 316L spazzolata*
- *Vetro di sicurezza temperato con bordi molati, extrachiaro ed antiriflesso resistente agli shock termici*
- *Pressacavo in plastica resistente agli agenti atmosferici, alla corrosione ed alle nebbie saline. Guarnizioni in silicone. Alimentatore esterno IP67 incluso*
- *Connettore IP68 per la connessione fra proiettore ed alimentatore incluso*
- *Connettori IP68 maschio e femmina e cavo in neoprene per prolunga connessione (fra proiettore ed alimentatore) accessori disponibili su richiesta*
- *Controcassa per installazione inclusa. Senza viti visibili*
- *Installazione in un'unica fase senza la necessità di aprire l'apparecchiatura*
- *Temperatura ambiente massima ammissibile +50°C per le versioni da 14W e 19W, +40°C per la versione da 25W*







HOUSING/ CONTROCASSA

IP67 F 20000 N IK08 CE Kg 1.65 A↑G D

Lamp / *Lampada*	Input / *Alimentazione*	Power / *Potenza*	Color Tolerance/ *Tolleranza Cromatica*	CRI / *CRI*
1 LED COB CREE	220/240V 50/60Hz	14 / 19 / 25W	2-SDCM / 3-SDCM	80 MIN



NEXO LUCE (Factory)
Strada Mirabella, 10
46040 Cavriana (MN), ITALY
T +39 0376 771513 F +39 0376 772235
sales@nexoluce.com www.nexoluce.com

© Nexo Luce, a company incorporated in Italy. The logo and the name are the property of Nexo Luce SRL. The present datasheet and its content in whole or in part are the property of Nexo Luce SRL. All rights reserved. We reserve the right to change details and specifications without prior written notice.



14W
3000 K 1748 lm
4000 K 1816 lm

19W
3000 K 2650 lm
4000 K 2752 lm

25W
3000 K 3362 lm
4000 K 3596 lm



14W
3000 K 1748 lm
4000 K 1816 lm

19W
3000 K 2650 lm
4000 K 2752 lm

25W
3000 K 3362 lm
4000 K 3596 lm



14W
3000 K 1748 lm
4000 K 1816 lm

19W
3000 K 2650 lm
4000 K 2752 lm

25W
3000 K 3362 lm
4000 K 3596 lm



14W
3000 K 1748 lm
4000 K 1816 lm

19W
3000 K 2650 lm
4000 K 2752 lm

25W
3000 K 3362 lm
4000 K 3596 lm



14W
3000 K 1748 lm
4000 K 1816 lm

19W
3000 K 2650 lm
4000 K 2752 lm

25W
3000 K 3362 lm
4000 K 3596 lm

*IP68 CONNECTORS ON REQUEST
**CONNETTORI IP68 SU RICHIESTA*
code: 003.0223.0

*2x0,35 H05RN-F CABLE (1 meter) ON REQUEST
CAVO 2X0,35 H05RN-F (1 metro) SU RICHIESTA
code: 003.0224.0

MAIN CODE *CODICE BASE*	RELEASE *EDIZIONE*	LIGHT COLOR *COLORE LUCE*	WATT *WATT*	OPTIC *OTTICA*	CONTROL *CONTROLLO*	FRAME COLOR *COLORE*
2568	**.1**	**B** 3000K	**.14** 14W	**.D** 20°	**1** ON/OFF	**.G** STAIN. STEEL / *INOX*
		C 4000K	**.19** 19W	**.F** 30°	**8** DIMMER 1-10V	
		* others on request / *altri su richiesta*	**.25** 25W	**.I** 48°		
				BZ 86°		
				CX ASYM 90°x45°		

CODE EXAMPLE : Projector with warm white light color at 3000K, 14W, 20° optic, ON/OFF control, stainless steel color
2568.1B.14.D1.G

ESEMPIO DI CODIFICA : Proiettore con luce calda a 3000K, 14W, ottica 20°, controllo ON/OFF, colore inox
2568.1B.14.D1.G

NEXO LUCE (Factory)
Strada Mirabella, 10
46040 Cavriana (MN), ITALY
T +39 0376 771513 F +39 0376 772235
sales@nexoluce.com www.nexoluce.com

© Nexo Luce, a company incorporated in Italy. The logo and the name are the property of Nexo Luce SRL. The present datasheet and its content in whole or in part are the property of Nexo Luce SRL. All rights reserved. We reserve the right to change details and specifications without prior written notice.