- Circular recessed LED downlight
- Aluminium body machined from solid in 6082 alloy with surface protection treatment and subsequent polyester powder paint resistant to corrosion, atmospheric conditions and salt spray
- Brushed stainless steel frame AISI 316L
- Thermal shock resistant tempered, extraclear, anti-glare safety glass with grinded edges
- Plastic cable gland resistant to corrosion, atmospheric conditions and salt spray
- Springs for ceiling installation
- IP67 external power supply included
- IP68 connector for the connection between projector and power supply included
- Maximum permissible ambient temperature + 50°C

- *Proiettore LED da incasso circolare*
- *Corpo in alluminio tornito dal pieno lega 6082 con trattamento superficiale di protezione e successiva verniciatura in polvere di poliestere resistente agli agenti atmosferici, alla corrosione ed alle nebbie saline*
- *Cornice esterna in acciaio inox AISI 316L spazzolata*
- *Vetro di sicurezza temperato con bordi molati, extrachiaro ed antiriflesso resistente agli shock termici*
- *Pressacavo in plastica resistente agli agenti atmosferici, alla corrosione ed alle nebbie saline*
- *Molle per installazione a soffitto*
- *Alimentatore esterno IP67 incluso*
- *Connettore IP68 per la connessione fra proiettore ed alimentatore incluso*
- *Temperatura ambiente massima ammissibile +50°C*





IP67 Kg 0.60 A G D

Lamp / *Lampada*	Input / *Alimentazione*	Power / *Potenza*	Color Tolerance/ *Tolleranza Cromatica*	CRI / *CRI*
1 LED COB CREE	220/240V 50/60Hz	5 / 10 / 14 / 19W	2-SDCM / 3-SDCM	80 MIN

Ø75mm

NEXO LUCE (Factory)
Strada Mirabella, 10
46040 Cavriana (MN), ITALY
T +39 0376 771513 F +39 0376 772235
sales@nexoluce.com www.nexoluce.com

© Nexo Luce, a company incorporated in Italy. The logo and the name are the property of Nexo Luce SRL. The present datasheet and its content in whole or in part are the property of Nexo Luce SRL. All rights reserved. We reserve the right to change details and specifications without prior written notice.

OMNIA P IN



ASYM
5W
3000 K 860 lm
4000 K 880 lm
10W
3000 K 1265 lm
4000 K 1316 lm
14W
3000 K 1748 lm
4000 K 1816 lm
19W
3000 K 2650 lm
4000 K 2752 lm



5W
3000 K 860 lm
4000 K 880 lm
10W
3000 K 1265 lm
4000 K 1316 lm
14W
3000 K 1748 lm
4000 K 1816 lm
19W
3000 K 2650 lm
4000 K 2752 lm



5W
3000 K 860 lm
4000 K 880 lm
10W
3000 K 1265 lm
4000 K 1316 lm
14W
3000 K 1748 lm
4000 K 1816 lm
19W
3000 K 2650 lm
4000 K 2752 lm



5W
3000 K 860 lm
4000 K 880 lm
10W
3000 K 1265 lm
4000 K 1316 lm
14W
3000 K 1748 lm
4000 K 1816 lm
19W
3000 K 2650 lm
4000 K 2752 lm



5W
3000 K 860 lm
4000 K 880 lm
10W
3000 K 1265 lm
4000 K 1316 lm
14W
3000 K 1748 lm
4000 K 1816 lm
19W
3000 K 2650 lm
4000 K 2752 lm

Finishing

STAIN.STEEL/ *INOX*

MAIN CODE *CODICE BASE*	RELEASE *EDIZIONE*	LIGHT COLOR *COLORE LUCE*	WATT *WATT*	OPTIC *OTTICA*	CONTROL *CONTROLLO*	FRAME COLOR *COLORE*
6694	**.1**	**B** 3000K	**.05** 10W	**.D** 20°	**1** ON/OFF	**G** STAIN. STEEL / *INOX*
		C 4000K	**.10** 10W	**.F** 30°	**8** DIMMER 1-10V	
		* others on request / *altri su richiesta*	**.14** 14W	**.I** 48°		
			.19 19W	**BZ** 86°		
				CX ASYM 90°x45°		

CODE EXAMPLE : Projector with warm white light color at 3000K, 10W, 20° optic, ON/OFF control, stainless steel color
6694.1B.10.D1.G

ESEMPIO DI CODIFICA : Proiettore con luce calda a 3000K, 10W, ottica 20°, controllo ON/OFF, colore inox
6694.1B.10.D1.G

NEXO LUCE (Factory)
Strada Mirabella, 10
46040 Cavriana (MN), ITALY
T +39 0376 771513 F +39 0376 772235
sales@nexoluce.com www.nexoluce.com

© Nexo Luce, a company incorporated in Italy. The logo and the name are the property of Nexo Luce SRL. The present datasheet and its content in whole or in part are the property of Nexo Luce SRL. All rights reserved. We reserve the right to change details and specifications without prior written notice.